



Visual contact outside



Manufactured in the EU



Cold-cut, crush-cut or ultrasonic



REACH compliant

TECHNICAL PROPERTIES		
Fabric Characteristic	Standard	
Composition	-	100 % PES
Weight (g/ m <sup>2</sup> )	EN 12127	82 ± 5 %
Thickness (mm)		0,29 ± 5 %
Light fastness (Xenotest grade)	ISO 105 B02:2002	≥ 6
Roll size		Width 250 cm, Length 30 m
Rapport		37,5 cm
colours		Brown, Grey, Ivory, White
Environmental & health properties	<b>Free and Forlamdehyde and lead</b> <b>Halogen Free.</b> <b>Reach Complain</b> <b>Oeko-tex standard 100</b> certified, which assures that no harmful substances are used during its production process	
Manufacturing properties	Cold cut, crush cut or ultrasonic Thermo welding by using adhesive tape Sew with double fold Manufacturing direction: ↓  Maximum tolerance in weft bow: 2,5°, slight deviations in horizontal lines may be spotted The weft bowing may be more evident in blinds installed next to each other	
Maintenance	Vacuum clean for regular maintenance Do not wash Do not rub Do not steam Do not dry clean	



Roller

**vertisol**  
shade fabrics

All specifications are based on average values and may deviate. The values are given for guidance and are not contractual.