



Formaldehyde-free



REACH compliant



Halogen-free



Manufactured in the EU



Cold-cut, crush-cut or ultrasonic



Visual contact outside

**TECHNICAL PROPERTIES**

Fabric Characteristic	Standard	
Composition	-	100 % PES
Weight (g/ m <sup>2</sup> )	EN 12127	107 ± 5 %
Thickness (mm)		0.26 ± 5 %
Light fastness	ISO 105 B02:2002	≥ 7
Rapport		20 cm
Roll size		30 m Length, 250 cm Width

**SUN CONTROL PROPERTIES**

Colour	% Tv	% Rv	% Av
QUARTZ	50	32	18
IVORY	47	31	22
JASPER	39	24	37
SILVER	38	29	33

Data measured according to internal method

**Environmental & health properties**

**Formaldehyde -free** and Lead-free.  
**Halogen free**  
BLISS is **Oeko-tex standard 100** certified, which assures that no harmful substances are used during its production process

**Manufacturing properties**

Always store rolls horizontally  
Cold-cut, crush-cut or ultrasonic  
Thermo welding by using adhesive tape.  
Sew with double fold  
Use back ladder support in pleated blinds  
Manufacturing Direction



Maximum tolerance in weft bow: 2,5° slight deviations in horizontal lines may be spotted  
The weft bowing may be more evident in blinds installed next to each other

