



Translucent



Ecological Fabric
REACH Compliant



Ultrasonic cut NOT
required



Manufactured in the EU

TECHNICAL PROPERTIES

Fabric Characteristic	Standard	
Composition	-	100% PES
Weight (g/ m ²)	EN 12127	125± 5%
Thickness (mm)	EN ISO 5084	0.24± 5%
Light Fastness	ISO 105 B02:2002	Base colour of the fabric 5/ 8 Print ≥6/8
Roll Size		30 m Length, 250 cm Width
Colours		Brick, Petrol, Slate, Ochre, Pine, White
Environmental & health properties	Free of formaldehyde and lead Halogen free Oeko-tex standard 100 certified	
Manufacturing properties	Always store rolls horizontally Cold cut, crush cut or ultrasonic. Manufacturing direction: ↓ Maximum tolerance in weft bow: 2,5 °, slight deviations in horizontal lines may be spotted. The weft bowing may be more evident in blinds installed next to each other	
Maintenance	Vacuum clean for regular maintenance Do not wash Do not rub Do not steam <div style="float: right; border: 1px solid black; padding: 2px;"> </div>	

An intrinsic characteristic of the fabrics could be the irregularity of the colour base. It could look little spots or little drops in the surface. These features are part of the nature of the design of the fabric and will not be considered as a fault.



vertisol
shade fabrics

*All specifications are based on average values and may deviate. The values are given for guidance and are not contractual.
Subject to technical modifications*

Expert Center:

vertisol
contemporary weavers

VERTISOL INT'L SRL
C-17, KM 18.92
08403 Granollers
SPAIN
T: + 34 93 840 1444
F: + 34 93 849 7219



ISO 9001:2015 and
ISO 14001:2015
certified company

Contact vertisol@vertisol.es for technical support