

# vertisol

# SOLPOR BO



Blackout




Manufactured in the EU



Cold-cut, crush-cut or ultrasonic



TECHNICAL PROPERTIES	
<b>Fabric Characteristic</b>	<b>Standard</b>
<b>Composition of raw fabric</b>	100 % PES
<b>Weight (g/ m<sup>2</sup>)</b>	400 ± 12 %
<b>Thickness (mm)</b>	0,6 ± 10 %
<b>Light fastness</b>	ISO 105 B02:2002 ( blue scale) Coating side ≥ 6 Colour side ≥ 5 White other colours ≥ 6
<b>Roll size</b>	Width 265 cm, Length 23 m
<b>Environmental &amp; health properties</b>	<b>Oeko-tex standard 100 certified</b>
<b>Handling and storage</b>	Rolls must be moved inside it external tube, or handled by two people, situated at 50 cm from each end Rolls must be stored totally flat. The extremes must not lay on edges It is recommended to roll and unroll the fabric by two people
<b>Manufacturing properties</b>	Always store rolls horizontally Cold-cut, crush-cut or ultrasonic It is recommended to keep a gap of 15 cm between the glazing and the blind It is recommended to used a 65 mm diameter tube Manufacturing direction: ↓
<b>Maintenance</b>	Vacuum clean for regular maintenance Do not wash Do not rub Do not steam Do not dry clean 

#### RANGE OF COLOURS 2022

White
Beige
Gris
Planta
Marengo
Marron



Roller and Panel Blinds

All specifications are based on average values and may deviate. The values are given for guidance and are not contractual.  
Subject to technical modifications

# vertisol

VERTISOL INT'L SRL  
C/Galileu Galilei, 68  
08403 Granollers  
SPAIN  
T: + 34 93 840 1444  
www.vertisol.com



ISO 9001:2015 and  
ISO 14001:2015  
certified company