

vertisol

STRIPES



Translucent



Cold-cut, crush-cut or ultrasonic



Manufactured in the EU

TECHNICAL PROPERTIES

Fabric Characteristic	Standard	
Composition		100 % PES
Weight (g/ m ²)		125 ± 5 %
Thickness (mm)		0.24 ± 5 %
Light fastness	ISO 105 B02:2002 (blue scale)	Fabric Base Print 5 ≥6
Roll size		30 m Length, 250 cm Width
Manufacturing properties	Always store rolls horizontally Cold-cut, crush-cut or ultrasonic Manufacturing direction: ↓ → Blinds can be manufactured 'drop to length' or railroaded, BUT the picture looks different if you manufactured in one direction or other Manufacture panel blinds only 'drop to length' ↓	
Maintenance	Vacuum clean for regular maintenance Do not wash Do not rub Do not steam	



RANGE OF COLOURS 2022

White

Green

Blue



Roller, and Panel Blinds

All specifications are based on average values and may deviate. The values are given for guidance and are not contractual. Subject to technical modifications

vertisol

VERTISOL INT'L SRL
 C/Galileu Galilei, 68
 08403 Granollers
 SPAIN
 T: + 34 93 840 1444
 www.vertisol.com



ISO 9001:2015 and
 ISO 14001:2015
 certified company