




FLAME RETARDANT

REACH COMPLIANT



IMO UPHOLSTERY CERTIFIED



MANUFACTURED IN THE EU



PHTHALATE FREE

	Standard	
Composition		73% PVC + 27% PES
Weight (g/m ²)	UNE EN 12127	518
Thickness (mm)	UNE EN ISO 5084:1997	0.88
Light Fastness (Grey scale)	EN ISO 105 B06-2002 (interior) EN ISO 105 B03:1994 (exterior) EN ISO 105 B04:1998 (exterior) EN ISO 4892-2 (exterior)	5/5 4/5 White
Light Fastness (Blue scale)	EN ISO 105 B02:2002 (interior)	8/8 7/8 white
Openness Factor %	Internal method	22.5
Breaking strength (daN/5cm)	EN ISO 1421:1999	Warp: 241 Weft: 226
Elongation at break (%)	EN ISO 1421:1999	Warp: 20.3 Weft: 19.9
Elongation at 20 daN (%)	EN ISO 1421:1999	Warp: 3.2 Weft: 3.4
Tearing Resistance (daN)	DIN 53363:2003	Warp: 31.4 Weft: 31.2
Abrasion Resistance	EN ISO 12947-2:1999/AC:2006	>300 000 cycles
Corrosion in saline environment neutral fog	EN ISO 112-017:92 ISO 9227:90	Without changes in surface (max.level)
Fire reaction	EN 1021-1:2006 /EN 1021-2:2006 IMO Resolution MSC.307(88)- (2010 FTP Code)and IMO MSC/Circ. 1102 NF P 92 503 DIN 4102:1 NFPA 701	Pass Pass M2 B2 Pass
Antibacterial Activity	ASTM 2180-01 and ASTM G21-09	Microorganism Growth Inhibition
Recycled content		2% Pre-consumer
Roll Size		width 210 cm length 50 m

Expert Center:

vertisol
contemporary weavers

VERTISOL INT'L SRL
C-17, KM 18.92
08403 Granollers
SPAIN
T: + 34 93 840 1444
F: + 34 93 849 7219



Contact vertisol@vertisol.es for technical support