

Product Specifications	Standard	Rolls & Tiles
Composition	-	75%vinyl + 25% polyester + backing 100% PVC
Weight (g/m²)	EN ISO 23997:2012	3300 g/m² +13% / -10%
Thickness (mm)	EN24346:2012	2.35 mm (+0.15mm/-0.1mm)
Light Fastness (Grey scale:1-5)	EN ISO 4892:2006 (exterior)	≥4/5
Light Fastness (Blue scale:1-8)	EN ISO 105 B02:2001 (interior)	≥7
Dimensional Stability %	EN ISO 23999:2012	Approved
Residual Indentation	EN ISO 24343-1:2012	<0.1mm
Sound Insulation	EN ISO 10140-3:2011	13 dB
Slip Resistance	EN 13893:2003	>0.35
Slip Resistance	DIN 51130:2014	R10
Fire Classification	IMO MSC.307 (88)	Pass
Corrosion in ambience of saline neutral fog		No changes after 240h exposure
Use Classification	ISO10874:2012	Heavy Commercial
Tile Dimensions	All colours are available in: <div style="display: flex; justify-content: space-around; align-items: flex-end;"> <div style="text-align: center;"> <p>Roll</p> <p>2mt</p> </div> <div style="text-align: center;"> <p>Square</p> <p>50cm/100cm</p> </div> <div style="text-align: center;"> <p>Plank</p> <p>25cm 75cm</p> </div> <div style="text-align: center;"> <p>Diamond</p> <p>50cm</p> </div> </div> <p>Recommended for tiles only. If in rolls, seams may be visible.</p>	

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications. The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

vertisol
contemporary weavers

C. 17Km. 18, 920-08403 Granollers (Barcelona), Spain
T. (+34) 93 840 14 44 · F. (+34) 93 849 72 19

fitnice® is a registered trademark of Vertisol Internacional SRL.

fitnice.com
info@fitnice.com

fitniceflooring