

vertisol®

THANE



Translucent




Manufactured in the EU



Cold-cut, crush-cut or ultrasonic



REACH compliant ecological fabric

TECHNICAL PROPERTIES		
Fabric Characteristic	Standard	
Composition	-	100 % PES
Weight (g/ m ²)	EN 12127	194 ± 5 %
Thickness (mm)		0.43 ± 5 %
Light fastness (Xenotest grade)	ISO 105 B02:2002	≥ 6
Roll size	Width 250 cm, Length 30 m	
Environmental & health properties	Formaldehyde-free and lead-free Reach compliant Oeko-tex standard 100 certified, which assures that no harmful substances are used during its production process	
Manufacturing properties	Always store rolls horizontally Cold-cut, crush-cut or ultrasonic Manufacturing direction:  Please note that Blinds can be manufactured 'drop to length' or railroaded, BUT the appearance is very different. Do not place in the same area blinds manufactured in different directions as this difference will be spotted. Maximum tolerance in weft bow: 2°, slight deviations in horizontal lines may be spotted The weft bowing may be more evident in blinds installed next to each other	
Maintenance	Vacuum clean for regular maintenance Do not wash Do not rub Do not steam Do not dry clean	

Colors
Finlandia
Tonga
Birmania
Suecia



Roller blinds



All specifications are based on average values and may deviate. The values are given for guidance and are not contractual.

Subject to technical modifications

vertisol

contemporary weavers

VERTISOL INT'L SRL
C-17, KM 18.92
08403 Granollers
SPAIN
T: + 34 93 840 1444
F: + 34 93 849 7219



ISO 9001:2015 and
ISO 14001:2015
certified company

Contact vertisol@vertisol.es for technical support