

vertisol

LINEN BO



Blackout



Cold-cut, crush-cut or Ultrasonic



Manufactured in the EU

TECHNICAL PROPERTIES

Fabric Characteristic	Standard	
Composition of raw fabric		94 % PES—6 % Li
Weight (g/ m ²)		400 ± 12 %
Thickness (mm)		0.53 ± 10 %
Light fastness	ISO 105 B02:2002 (blue scale)	≥ 6
Roll width and length		270 cm and 23 m
Environmental & health properties		Oeko-tex standard 100 certification
Handling and storage	Always store rolls horizontally Rolls must be moved inside it external tube, or handled by two people, situated at 50 cm from each end Rolls must be stored totally flat. The extremes must not lay on edges It is recommended to roll and unroll the fabric by two people	
Manufacturing properties	Cold-cut, crush-cut or ultrasonic It is recommended to keep a gap of 15 cm between the glazing and the blind Manufacturing direction could be produced in both direction, BUT do not place in the same area blinds manufactured in different directions as this difference will be spotted Manufacture panel blinds only 'drop to length'	
Maintenance	Vacuum clean for regular maintenance Do not wash Do not rub Do not steam Do not dry clean Wipe gently with a wet sponge 	

RANGE OF COLOURS 2022

Natural

Beige

Gris



Roller and Panel Blinds

All specifications are based on average values and may deviate. The values are given for guidance and are not contractual. Subject to technical modifications

vertisol

VERTISOL INT'L SRL
C/Galileu Galilei, 68
08403 Granollers
SPAIN
T: + 34 93 840 1444
www.vertisol.com



ISO 9001:2015 and
ISO 14001:2015
certified company