

Product Specifications	Standard	Tiles	Raised Access Floor Tiles (Square and Plank)
<b>Composition</b>	-	91%vinyl + 9% polyester + backing100% vinyl	91%vinyl + 9% polyester + backing100% vinyl
<b>Weight (g/m<sup>2</sup>) (oz/sq ft)</b>	ISO 8543:1998	3500 g/m <sup>2</sup> (11.5 oz/sq ft) +13% / -10%	4275 g/m <sup>2</sup> (14.0 oz/sq ft) +13% / -10%
<b>Thickness (mm) (in)</b>	ISO 1765:1986	2.70 mm (0.11 in)	3.35 mm (0.13 in)
<b>Light Fastness (Grey scale: 1-5)</b>	EN ISO 4892:2006 (exterior)	>4/5	>4/5
<b>Light Fastness (Blue scale: 1-8)</b>	EN ISO 105B02:2001 (interior)	>7/8	>7/8
<b>Dimensional Stability %</b>	EN ISO 23999:2012	≤0.25%	≤0.25%
<b>Residual Indentation</b>	EN ISO 24343-1:2012	<0.30 mm (<0.011 in)	<0.30 mm (<0.011 in)
<b>Castor Chair Test</b>	EN 985:2002	Intensive use	Intensive use
<b>Sound Insulation</b>	EN ISO 10140-3:2011	14 dB	15 dB
<b>Thermal Resistance</b>	EN 12667:2001	< 0.15m <sup>2</sup> K/W	< 0.15m <sup>2</sup> K/W
<b>Static Electricity</b>	EN 1815:1997	< 2 kV	< 2 kV
<b>Slip Resistance</b>	EN 13893:2003	>0.4	>0.4
<b>Slip Resistance</b>	DIN 51130:2014	R9	R9
<b>Slip Resistance</b>	ASTM C1028-96 Static Coefficient	Wet: 0.59; Dry: 0.72	Wet: 0.59; Dry: 0.72
<b>Fire Classification</b>	EN 13501-1:2007	Bfl-S1	Bfl-S1
<b>Fire Classification</b>	ASTM E648 (NFPA 253)	Class 1	Class 1
<b>Antibacterial activity</b>	ASTM E 2180-18 ASTM G21:2013	Inhibition of bacterial growth & Antifungal activity	Inhibition of bacterial growth & Antifungal activity
<b>CE Certificate</b>	EN 14041:2004	2895-CPR-SH00981	2895-CPR-SH00981
<b>Use Classification</b>	EN 1307:2014	Heavy Commercial	
<b>Tile Dimensions</b>			