


MOD BO



Blackout



Manufactured in the EU



46 % Recycled PET



Cold-cut, crush-cut or ultrasonic



TECHNICAL PROPERTIES

Fabric Characteristic	Standard	
Composition fabric		54 % PES 46% Recycled PET
Weight (g/ m ²)		370 g/ m ² ± 12 %
Thickness (mm)		0.45 mm ± 10 %
Light fastness	ISO 105 B02:2002 (blue scale level)	Coating side ≥ 6 Color side ≥ 6
Roll size		Width 265 cm, Length 23 m
Handling and storage	Rolls must be moved inside it external tube, or handled by two people, situated at 50 cm from each end Rolls must be stored totally flat. The extremes must not lay on edges It is recommended to roll and unroll the fabric by two people	
Manufacturing properties	Always store rolls horizontally Cold-cut, crush-cut or ultrasonic It is recommended to keep a gap of 15 cm between the glazing and the blind It is recommended to used a 65 mm diameter tube Manufacturing direction: ↓	
Maintenance	Vacuum clean for regular maintenance Do not wash Do not rub Do not steam Do not dry clean	

White

Nacar

Jade

Onix

Topaz

Agate



Roller Blinds

All specifications are based on average values and may deviate. The values are given for guidance and are not contractual.
Subject to technical modifications

vertisol

VERTISOL INT'L SRL
C/Galileo Galilei, 68
08403 Granollers
SPAIN
T: + 34 93 840 1444
www.vertisol.com



ISO 9001:2015 and
ISO 14001:2015
certified company