

| Product Specifications | Standard | Rolls & Tiles (Rolls only for corridors) |
|---|--|--|
| Composition | - | 84% vinyl + 16% polyester + backing 100% vinyl |
| Weight (g/m²) (oz/sq ft) | ISO 8543:1998 | 3100 g/m² (10.2 oz/sq ft) +13% / -10% |
| Thickness (mm.) (in) | ISO 1765:1986 | 2.30 mm (0.09 in) |
| Light Fastness (Grey scale: 1-5) | EN ISO 4892:2006 (exterior) | >4/5 |
| Light Fastness (Blue scale: 1-8) | EN ISO 105B02:2001 (interior) | >7/8 |
| Dimensional Stability % | EN ISO 23999:2012 | ≤0.25% |
| Castor Chair Test | EN 985:2002 | Intensive use |
| Sound Insulation | EN ISO 10140-3:2011 | 12 dB |
| Thermal Resistance | EN 12667:2001 | < 0.15m² K/W |
| Static Electricity | EN 1815:1997 | < 2 kV |
| Slip Resistance | EN 13893:2003 | >0.4 |
| Slip Resistance | DIN 51130:2014 | R10 |
| Slip Resistance | ASTM C1028-96 Static Coefficient | Wet: 0.79; Dry: 0.86 |
| Fire Classification | EN 13501-1:2007 | Bfl-S1 |
| Fire Classification | ASTM E648 (NFPA 253) | Class 1 |
| Antibacterial activity | ASTM E 2180-18 ASTM G21:2013 | Inhibition of bacterial growth & Antifungal activity |
| Roll Width | - | 200 cm 78.740 in |
| Roll Length | - | 10 lm (32.81 ft) 20 lm (65.62 ft) |
| CE Certificate | EN 14041:2004 | 2895-CPR-SH00981 |
| Use Classification | EN 1307:2014 | Heavy Commercial |
| Tile Dimensions | <div style="display: flex; justify-content: space-around; text-align: center;"> <div> <p>Square</p> <p>50cm/100cm</p> </div> <div> <p>Plank</p> <p>25cm 76cm</p> </div> <div> <p>Brick</p> <p>50cm 100cm</p> </div> <div> <p>Diamond</p> <p>50cm 50cm</p> </div> <div> <p>Hexagon</p> <p>61.4cm 30.7cm</p> </div> <div> <p>E. Triangle</p> <p>50cm</p> </div> <div> <p>I. Triangle</p> <p>50cm 30.7cm</p> </div> <div> <p>Trap</p> <p>61.4cm 27cm</p> </div> <div> <p>Arcade</p> <p>75cm 50cm</p> </div> </div> | |

C.17Km.18,920-08403 Granollers (Barcelona), Spain
T. (+34) 93 840 14 44 · F. (+34) 93 849 72 19
www.vertisol.com

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications.

The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

Some of the test and certifications present in this TDS can be found under the name Fitnice Floor

