














# CHROMA ACOUSTIC TECHNICAL DATA SHEET

	Standard	Chroma Acoustic
 <b>Composition</b>	-	Fabric 94% Vinyl + 6% polyester Backing 85% vinyl + Felt PES 15%
 <b>Weight (g/m<sup>2</sup>) (guidance data)</b>	-	3800 g/m <sup>2</sup> +13% / -10%
 <b>Thickness (mm) (guidance data)</b>	-	4,56mm +10% / -10%
 <b>Light Fastness (Grey scale: 1-5)</b>	EN ISO 4892:2006 (exterior)	5/5 White 4/5
 <b>Light Fastness (Blue scale: 1-8)</b>	EN ISO 105B02:2001 (interior)	8/8 White 7/8
 <b>Dimensional Stability %</b>	EN ISO 23999:2012	≤ 0.25
 <b>Castor Chair Test</b>	EN 985:2002	Intensive Use
 <b>Static Electricity</b>	EN 1815:1997	< 2 Kv
 <b>Thermal Resistance</b>	EN 12667:2001	< 0.15m <sup>2</sup> K/W
 <b>Sound Insulation</b>	EN ISO 10140-3:2021	23 dB
 <b>Slip Resistance</b>	EN 13893:2003	>0.3
 <b>Fire Classification</b>	EN 13501-1:2007	Bfls1
<b>Use Classification</b>	EN 1307:2014	Heavy Commercial 
<b>CE Certificate</b>	2895-CPR-SH00981	
<b>Florescore Certification</b>	SCS-FS-03251	
<b>Tile Dimensions</b>	Square 50x50 cm	
<b>PVC Formulation Antimony Free and Phthalate Free</b>		

## vertisol

C.17Km.18,920-08403 Granollers (Barcelona), Spain  
T. (+34) 93 840 14 44 · F. (+34) 93 849 72 19  
www.vertisol.com

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications.  
The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.  
Some of the test and certifications present in this TDS can be found under the name Fitnice Floor

