




FLAME RETARDANT



REACH COMPLIANT
MANUFACTURED IN THE EU



IMO UPHOLSTERY CERTIFIED



	Standard	
Composition		73% PVC + 27% PES
Weight (g/m ²)		530
Thickness (mm)		0.88
Light Fastness (Grey scale)	EN ISO 4892-2 (exterior) (grey scale level)	5/5 4/5 White
Light Fastness (Blue scale)	EN ISO 105 B02:2002 (interior) (blue scale level)	8/8 7/8 white
Openness Factor %		25
Breaking strength (daN/5cm)	EN ISO 13934-1:1999	Warp: 252 Weft: 237
Elongation at break (%)	EN ISO 1421:2017	Warp: 21.5 Weft: 20
Elongation at 20 daN (%)	EN ISO 1421:1999	Warp: 1.8 Weft: 1.7
Tearing Resistance (daN)	EN ISO 13937-3:2001	Warp: 19.3 Weft: 18.9
abrasión Resistance	EN ISO 12947-2:1999/AC:2006	>300 000 cycles
Fire reaction	EN 1021-1:2006 /EN 1021-2:2006 NFPA 701	Pass Pass
	IMO Resolution MSC.307(88)- (2010 FTP Code)and IMO MSC/Circ. 1102	Pass
Recycled content		2% Pre-consumer
Roll Size		width 210 cm length 50 m

All specifications are based on average values and may deviate. The values are given for guidance and are not contractual. Subject to technical modifications