## vertisol

## **THANE**



Translucent



Manufactured in the EU



Cold-cut, crush-cut or ultrasonic

TECHNICAL PROPERTIES	
Fabric Characteristic	Standard
Composition	100 % PES
Weight (g/ m²)	194 ± 5 %
Thickness (mm)	0.43 ± 5 %
Light fastness ISO 105 B02:2002( blue scale)	≥ 6
Roll size	Width 270 cm, Length 30 m
Environmental & health properties	Oeko-tex standard 100 certified
Manufacturing properties	Always store rolls horizontally Cold-cut, crush-cut or ultrasonic Manufacturing direction:  Please note that Blinds can be manufactured 'drop to length' or railroaded, BUT the appearance is very different. Do not place in the same area blinds manufactured in different directions as this difference will be spotted.  Maximum tolerance in weft bow: 2°, slight deviations in horizontal lines may be spotted.  The weft bowing may be more evident in blinds installed next to each other
Maintenance	Vacuum clean for regular maintenance Do not wash Do not rub Do not steam Do not dry clean

RANGE OF COLOURS
Finlandia
Suecia
Tonga
Birmania



Roller Blinds

All specifications are based on average values and may deviate. The values are given for guidance and are not contractual. Subject to technical modifications



VERTISOL INT'L SRL C/Galileu Galilei, 68 08403 Granollers SPAIN T: + 34 93 840 1444 www.vertisol.com





ISO 9001:2015 and ISO 14001:2015 certified company